

0,22,24,25

9. 5,037,172, Aug. 6, 1991, Fiber ~~Best Available Copy~~ reflective notch coupler; Edwin D. Hekman, et al., 385/31 , 123 [IMAGE AVAILABLE]

22. 4,307,932, Dec. 29, 1981, Arrangement for detecting a branched off signal; Gerhard Winzer, 385/48 ; 257/432; 385/39 , 49 [IMAGE AVAILABLE]

24. 4,173,390, Nov. 6, 1979, Fiber optic T-coupler; Alfred Kach, 385/44 ; 359/173; 385/33 , 47 , 51 , 88 [IMAGE AVAILABLE]

25. 3,589,795, Jun. 29, 1971, FIBER OPTICS ELEMENT WITH OBLIQUE INTERNAL REFLECTOR MEANS; Eiichi Miyazaki, et al., 385/120 ; 313/475; 385/119 [IMAGE AVAILABLE]

=> d his

(FILE 'USPAT' ENTERED AT 11:44:55 ON 21 MAY 93)

L1 9100 S 385??/CCLSF
L2 1414 S FIBRE(P)NOTCH? OR FIBER(P)NOTCH?
L3 196 S L1 AND L2
L4 1739 S REFLECT?(P)NOTCH?
L5 25 S L3 AND L4

=>

950'896/40